§ 1.136(a), and any fees required therefor (including fees for net addition of claims) are hereby authorized to be charged to our Deposit Account No. 19-0036.

Amendments

In the Specification:

Please substitute pending paragraph [0096] with the following paragraph [0096]:

Poloxamers of the present invention include, but are not limited to commercially available poloxamers such as Pluronic® L121 (ave. MW: 4400; approx. MW of hydrophobe, 3600; approx. wt. % of hydrophile, 10%), Pluronic® L101 (ave. MW: 3800; approx. MW of hydrophobe, 3000; approx. wt. % of hydrophile, 10%), Pluronic® L81 (ave. MW: 2750; approx. MW of hydrophobe, 2400; approx. wt. % of hydrophile, 10%), Pluronic® L61 (ave. MW: 2000; approx. MW of hydrophobe, 1800; approx. wt. % of hydrophobe, 900; approx. wt. % of hydrophobe, 10%), Pluronic® L31 (ave. MW: 1100; approx. MW of hydrophobe, 900; approx. wt. % of hydrophobe, 3600; approx. wt. % of hydrophile, 20%), Pluronic® L92 (ave. MW: 3650; approx. MW of hydrophobe, 2700; approx. wt. % of hydrophile, 20%), Pluronic® L72 (ave. approx. MW of hydrophobe, 2700; approx. wt. % of hydrophile, 20%), Pluronic® L72 (ave.

MW: 2750; approx. MW of hydrophobe, 2100; approx. wt. % of hydrophile, 20%),

Pluronic® L62 (ave. MW: 2500; approx. MW of hydrophobe, 1800; approx. wt. % of

hydrophile, 20%), Pluronic® L42 (ave. MW: 1630; approx. MW of hydrophobe, 1200;

approx. wt. % of hydrophile, 20%), Pluronic® L63 (ave. MW: 2650; approx. MW of

hydrophobe, 1800; approx. wt. % of hydrophile, 30%), Pluronic® L43 (ave. MW: 1850;

approx. MW of hydrophobe, 1200; approx. wt. % of hydrophile, 30%), Pluronic® L64 (ave.



MW: 2900; approx. MW of hydrophobe, 1800; approx. wt. % of hydrophile, 40%), Pluronic® L44 (ave. MW: 2200; approx. MW of hydrophobe, 1200; approx. wt. % of hydrophile, 40%), Pluronic® L35 (ave. MW: 1900; approx. MW of hydrophobe, 900; approx. wt. % of hydrophile, 50%), Pluronic® P123 (ave. MW: 5750; approx. MW of hydrophobe, 3600; approx. wt. % of hydrophile, 30%), Pluronic® P103 (ave. MW: 4950; approx. MW of hydrophobe, 3000; approx. wt. % of hydrophile, 30%), Pluronic® P104 (ave. MW: 5900; approx. MW of hydrophobe, 3000; approx. wt. % of hydrophile, 40%), Pluronic® P84 (ave. MW: 4200; approx. MW of hydrophobe, 2400; approx. wt. % of hydrophile, 40%), Pluronic® P105 (ave. MW: 6500; approx. MW of hydrophobe, 3000; approx. wt. % of hydrophile, 50%), Pluronic® P85 (ave. MW: 4600; approx. MW of hydrophobe, 2400; approx. wt. % of hydrophile, 50%), Pluronic® P75 (ave. MW: 4150; approx. MW of hydrophobe, 2100; approx. wt. % of hydrophile, 50%), Pluronic® P65 (ave. MW: 3400; approx. MW of hydrophobe, 1800; approx. wt. % of hydrophile, 50%), Pluronic® F127 (ave. MW: 12600; approx. MW of hydrophobe, 3600; approx. wt. % of hydrophile, 70%), Pluronic® F98 (ave. MW: 13000; approx. MW of hydrophobe, 2700; approx. wt. % of hydrophile, 80%), Pluronic® F87 (ave. MW: 7700; approx. MW of hydrophobe, 2400; approx. wt. % of hydrophile, 70%), Pluronic® F77 (ave. MW: 6600; approx. MW of hydrophobe, 2100; approx. wt. % of hydrophile, 70%), Pluronic® F108 (ave. MW: 14600; approx. MW of hydrophobe, 3000; approx. wt. % of hydrophile, 80%), Pluronic® F98 (ave. MW: 13000; approx. MW of hydrophobe, 2700; approx. wt. % of hydrophile, 80%), Pluronic® F88 (ave. MW: 11400; approx. MW of hydrophobe, 2400; approx. wt. % of hydrophile, 80%), Pluronic® F68 (ave. MW: 8400; approx. MW of





hydrophobe, 1800; approx. wt. % of hydrophile, 80%), Pluronic® F38 (ave. MW: 4700; approx. MW of hydrophobe, 900; approx. wt. % of hydrophile, 80%).

Please substitute pending paragraph [0097] with the following paragraph [0097]:

[0097]

Reverse poloxamers of the present invention include, but are not limited to Pluronic® R 31R1 (ave. MW: 3250; approx. MW of hydrophobe, 3100; approx. wt. % of hydrophile, 10%), Pluronic® R 25R1 (ave. MW: 2700; approx. MW of hydrophobe, 2500; approx. wt. % of hydrophile, 10%), Pluronic® R 17R1 (ave. MW: 1900; approx. MW of hydrophobe, 1700; approx. wt. % of hydrophile, 10%), Pluronic® R 31R2 (ave. MW: 3300; approx. MW of hydrophobe, 3100; approx. wt. % of hydrophile, 20%), Pluronic® R 25R2 (ave. MW: 3100; approx. MW of hydrophobe, 2500; approx. wt. % of hydrophile, 20%), Pluronic® R 17R2 (ave. MW: 2150; approx. MW of hydrophobe, 1700; approx. wt. % of hydrophile, 20%), Pluronic® R 12R3 (ave. MW: 1800; approx. MW of hydrophobe, 1200; approx. wt. % of hydrophile, 30%), Pluronic® R 31R4 (ave. MW: 4150; approx. MW of hydrophobe, 3100; approx. wt. % of hydrophile, 40%), Pluronic® R 25R4 (ave. MW: 3600; approx. MW of hydrophobe, 2500; approx. wt. % of hydrophile, 40%), Pluronic® R 22R4 (ave. MW: 3350; approx. MW of hydrophobe, 2200; approx. wt. % of hydrophile, 40%), Pluronic® R 17R4 (ave. MW: 3650; approx. MW of hydrophobe, 1700; approx. wt. % of hydrophile, 40%), Pluronic® R 25R5 (ave. MW: 4320; approx. MW of hydrophobe, 2500; approx. wt. % of hydrophile, 50%), Pluronic® R 10R5 (ave. MW: 1950; approx. MW of hydrophobe, 1000; approx. wt. % of hydrophile, 50%), Pluronic® R 25R8 (ave. MW: 8550; approx. MW of hydrophobe, 2500; approx. wt. % of hydrophile, 80%), Pluronic® R 17R8 (ave. MW: 7000; approx. MW of hydrophobe, 1700; approx. wt. % of hydrophile, 80%), and

